


Project F.

© 7778 Last modified by the author on 16/05/2018 - 18:18



2



A

Building Type : Isolated or semi-detached house
Construction Year : 2016
Delivery year : 2017
Address 1 - street : 4041 VOTTEM, Belgique
Climate zone : [Cfb] Marine Mild Winter, warm summer, no dry season.

Net Floor Area : 96 m²
Construction/refurbishment cost : 136 000 €
Number of Dwelling : 1 Dwelling
Cost/m2 : 1416.67 €/m²

General information

This is a single-family dwelling project for a couple with a child. From the beginning, the owners wanted to design a sustainable building of simple shape, simplified use, energy efficient and composed of healthy materials, with a tight overall budget. A detached car-port street and the positioning of the dwelling on the flat part of the land, slightly back and overhang, generate a sense of intimacy and have reduced excavations. The volumetry is simple and frank, the raw materials and textures and in reduced number. Emphasis was placed on energy efficiency and formal simplicity. It is a house to live with its own personality.

If you had to do it again?

The Eternit panel siding was quite complex to achieve for a perfect layout and to adjust the joints; the light color accentuates the small defects.

Data reliability

Assessor

Stakeholders

Contractor

Name : Eric Franquet
Contact : ericvottem@hotmail.com

Construction Manager

Name : FuturHome
Contact : info@futurhome.be
<http://www.futurhome.be>

Stakeholders

Function : Designer
Olivier Davids

olivier.davids@skynet.be

Contracting method

Lump-sum turnkey

Owner approach of sustainability

Achieve an autonomous dwelling in terms of annual energy consumption for heating and hot water needs. Use sustainable materials within budget and technical possibilities.

Architectural description

This is a single-family dwelling project for a couple with a child. From the beginning, the owners wanted to design a sustainable building of simple shape, simplified use, energy efficient and composed of healthy materials, with a tight overall budget. A detached car-port street and the positioning of the dwelling on the flat part of the land, slightly back and overhang, generate a sense of intimacy and have reduced excavations. The volumetry is simple and frank, the raw materials and textures and in reduced number. Emphasis was placed on energy efficiency and formal simplicity. It is a house to live with its own personality.

Energy

Energy consumption

Primary energy need : 75,00 kWh/m².an
Primary energy need for standard building : 115,00 kWh/m².an
Calculation method :
CEEb : 0.0003
Final Energy : -6,00 kWh/m².an
Breakdown for energy consumption :
Heating: 1.371 kWh/an - ECS: 1.457 kWh/year

Envelope performance

More information :
The envelope is composed of a load-bearing part in cross-laminated wood panels -CLT- on which is fixed a secondary structure in prefabricated wooden beams of Steico Wall type on 36cm thick; this structure is closed using wood fiber panels type Steico Universal 3,5cm thick. Cellulose wadding is then blown into the wells thus formed.

Indicator :
Air Tightness Value : 0,30
Users' control system opinion :
Complete home automation.

Renewables & systems

Systems

Heating system :

- No heating system

Hot water system :

- Heat pump

Cooling system :

- No cooling system

Ventilation system :

- Double flow heat exchanger

Renewable systems :

- Solar photovoltaic

Renewable energy production : 120,00 %

In annual report, the photovoltaic installation covers the necessary needs in heating and hot water production. The surplus is devoted to domestic electricity consumption.

Environment

Urban environment

Dense urban fabric, well served in services, local shops and transport offer.

Land plot area : 285,00 m²

Built-up area : 19,00 %

Products

Product

Cross-laminated wood structure

Eugen Decker


info@hochwald.com

<http://www.eugen-decker.de>

Product category : Gros œuvre / Structure, maçonnerie, façade

Complete structure of the building in cross-laminated wood panels -CLT-, the wood species used being spruce.

Speed of execution - mounted in two days. The choice fell on a prefabrication company CLT not too far from the site in order to remain in an overall approach of acceptable sustainability.



Double flux ventilation

Zehnder

jean-francois.schmitz@zehndergroup.com

<https://www.zehnder.be>

Product category : Génie climatique, électricité / Ventilation, rafraîchissement

MVC dual flow Zehnder Comfod 250 with electric heater

In the context of this passive project, the installation of a dual flow ventilation unit was of course mandatory. Occupants quickly realized the qualities and usefulness of the system and the calculations showed that the installation of a heating system was superfluous and that the installation of a heating battery alone could meet the demand.



Passive exterior joinery

Pural


info@pural-profile.de

<https://www.pural-profile.de/>

Product category : Second œuvre / Menuiseries extérieures

The aluminum exterior joinery comes from Pural Eco 90 series. This profile has been awarded by the PassivHaus Institute. The range is quite small but this system offers a value for money very interesting.

We benefited from the skills of Carpentry Peters in Weywertz, with whom we developed all the constructive details in order to best meet the PHPP calculations. The Eco 90 series is very robust and offers several interesting options such as the invisible hinges (chosen for this project) and the chassis foot profiles to make connections without thermal bridges and facilitating the installation of waterproofing membranes.



Underfloor insulation

Jackon Insulation

kristof.beatse@jackodur.com

<https://www.jackon-insulation.com>

Product category : Gros œuvre / Système passif

Underfloor insulation in extruded polystyrene -XPS-, on a thickness of 32cm.

The complete packing of the supporting raft made of reinforced concrete with the help of system really makes it possible to protect itself from any constructive knot, while preserving the benefit of the thermal inertia of the concrete on the side of the protected volume. Once the concrete cleans executed on the stonework, the installation of this insulating raft required a small day of intervention. All the tightenings around the technical ducts crossing the insulating raider have been carefully executed.



Sealing membranes

Siga

info@siga.ch

<http://www.siga.ch>

Product category :

The set of airtight joints was made using Siga products, known for their durability and the preservation of their technical qualities over time. Siga Rissan for the shell, Siga Fentrim for the exterior joinery.



A first sealing barrier was generated at the junction of the constructive panels, on the inside. A second doubling barrier was then placed on the outside of the panels.

Platform waterproofing membrane

Sika

info@sika.be

<https://bel.sika.com>

Product category : Gros œuvre / Charpente, couverture, étanchéité

Cover of the platform using a Sika Sarnafil polyolefin membrane, extremely durable. The laying of this hot-welded membrane does not require any form of slope and the tightness is guaranteed until the wall-covering.



Weighted membrane with rolled gravel, of light color.

Costs

Construction and exploitation costs

Renewable energy systems cost : 7 250,00 €

Carbon

GHG emissions

Building lifetime : 75,00 an(s)

Life Cycle Analysis

Eco-design material :

Support structure in cross-laminated wood panels -CLT-; Steico Universal fiberglass closure panels; Isocell cellulose wadding insulation

Contest

Reasons for participating in the competition(s)

The project is designed on the passive standard. The contemporary intention is frank and simple. To optimize the compactness of the project, a car-port with a green roof is laid out in front. It is part of a dense urban fabric, well served by services, local shops and transport offer. **The use of sustainable materials was emphasized :** laminated timber structure, use of durable insulation (cellulose wadding, cork, fibreboard), cellulose floor and lining plates, lack of wall finishing and interior ceilings (spruce wood left exposed), untreated wood flooring, use of environmentally friendly paints, FPO roofing deck membrane. **Simplification of the technical installations :** absence of heating system except the presence of a heating battery on the MVC, complete home automation. **Installation** of photovoltaic electricity production of 3.75 kWp, covering the totality of the annual energy needs for the heating (1.371 kWh / year), domestic hot water production (1,457 kWh / year) as well as a portion of domestic electricity consumption; **the project can thus be described as energetically positive in the annual balance sheet (excluding domestic electricity consumption).** **Gross building data: Annual heating requirement according to PHPP: 14 kWh / m²a (15 kWh / m²a max.) Annual requirement in primary energy according to PHPP: 75.8 kWh / m²a (120 kWh / m²a max.) Frequency of overheating according to PHPP: 5.3% (10% max). Results of the airtightness test before finalization: n50: 0,19 l / h (0,6 l / h max.) According to EN 13829, method A Results of the final air tightness test: 0, 3 l / h (max. 0.6 l / h) according to EN 13829, method A**

Building candidate in the category





Energie & Climats Tempérés



Coup de Cœur des Internautes