House in Muros. Certified Passivhaus.

by Amaya Salinas de León / 🕔 2016-06-03 11:39:59 / Spagna / 💿 13132 / 🍽 ES

New Construction	Primary energy need : 14.9 kWhpe/m ² .year (Calculation method : Primary energy needs)
	ENERGY CONSUMPTION Economical building < 50 A 51 à 90 B 91 à 150 C 151 à 230 D 231 à 330 E 331 à 450 F > 450 G Energy-intensive building

 Building Type : Isolated or semi-detached house

 Construction Year : 2015

 Delivery year : 2015

 Address 1 - street : Reborio 57 M 33138 MUROS DE NALóN, España

 Climate zone : [Cfc] Marine Cool Winter & summer- Mild with no dry season.

Net Floor Area : 200 m² Construction/refurbishment cost : 1 200 € Number of Dwelling : 1 Dwelling Cost/m2 : 6 €/m²

Certifications :



General information

Detached house situated in Muros del Nalon that integrates both the concepts of the Passivhaus standard energy efficiency and bioclimatic architecture. This way the building guarantees an almost zero energy consumption. The housing is formed by two different volumes, which are arranged according to different orientations, the prevailing winds and views, and are adapted to the shape of the plot and alignments marked by urban planning. The north facade is almost blind, avoiding energy losses. South façade has large windows in the living room, kitchen and master bedroom, promoting solar gains in winter. In summer the house is protected by shadings and temporary protections. As for the materials used, the architecture of the fishing villages of the Asturian western coast, are formed by volumes of different colors and wooden galleries. These two materials are reinterpreted and are used to coat the housing: the volumes where the rooms are located are coated externally with continuous Siberian Larch wood both façade and roof. These wooden pieces are based on a white pedestal in which day and access areas are located.

See more details about this project

http://www.amayasalinas.com

Data reliability

3rd part certified

Stakeholders

Stakeholders

Function : Designer Amaya Salinas de León Arquitecta

C http://www.amayasalinas.com Writing Project and Passivhaus calculations

Function : Contractor TimberOnLive s.I.

Chttp://www.timberonlive.com Construction company

Function : Certification company Energiehaus s.I.

Attp://www.energiehaus.es Passivhaus Certificate

Contracting method

Lump-sum turnkey

Owner approach of sustainability

Detached house situated in Muros del Nalon that integrates both the concepts of the Passivhaus standard energy efficiency and bioclimatic architecture. This way the building guarantees an almost zero energy consumption. The house is projected according to the criteria of the standard Passivhaus, in a way that energy consumption is adapted to the unique operation of housing. This way, the two volumes, can operate independently and have an energy consumption depending on the different degrees of occupancy of the house.

Architectural description

The housing is formed by two different volumes, which are arranged according to different orientations, the prevailing winds and views, and are adapted to the shape of the plot and alignments marked by urban planning. The north facade is almost blind, avoiding energy losses. South façade has large windows in the living room, kitchen and master bedroom, promoting solar gains in winter. In summer the house is protected by shadings and temporary protections.

Energy

Energy consumption

Primary energy need : 14,90 kWhpe/m².year Primary energy need for standard building : 99,00 kWhpe/m².year Calculation method : Primary energy needs CEEB : 0.0701

Envelope performance

Envelope U-Value : 0,18 W.m⁻².K⁻¹ More information : Larch ventilated exterior wall: 0.176 w / mk Larch ventilated cover : 0.193 w / mk Flat roof: 0.116 w / mk Foundation slab: 0.181 w / mk

Real final energy consumption

Real final energy consumption/m2 : 99,00 kWhfe/m².year

Renewables & systems

Systems

Heating system :

Wood boiler

Hot water system :

• Heat pump

Cooling system :

No cooling system

Ventilation system :

- Natural ventilation
- Nocturnal ventilation
- Free-cooling
- Double flow heat exchanger

Renewable systems :

- Biomass boiler
- Heat pump

Environment

GHG emissions

GHG in use : 25,90 KgCO₂/m²/year Methodology used : PHPP 8.4

Building lifetime : 50,00 year(s)

Indoor Air quality

The house is equipped with a mechanical ventilation system controlled double-flow ventilation (balanced passive house). The heat exchanger installed is the Siber DF4 Excellent model, certified by the Passivhaus Institute with a yield of 84% and a maximum ventilation capacity of 400 m3 / h. The nominal performance of this system, taking into account losses in the ducts between the heat recovery device and the thermal envelope is 83%. Outside air ducts (input and output) are isolated and out to facade. The heat exchanger, is placed in the utility room on the ground floor, outside the thermal envelope. The supply and exhaust pipes run both ground floor and first floor by the wrought facilities coffin is insulated with rock wool 12 cm thick. of thickness. Air supply grilles are placed directly on the floor and are located in the living room and bedrooms, and extraction grilles are placed on the walls to 30cm from the ceiling in the bathrooms and kitchen.

Comfort

Health & comfort : Thanks to proper insulation, airtightness and mechanical ventilation double flow own homes certified Passivhaus great interior comfort and low CO2 concentration is achieved inside.

Products

Product

Recuperador de calor Siber DF Excellent

Siberzone s.l.

siber@siberzone.es

http://www.siberzone.es

Product category : HVAC / Ventilazione, Raffrescamento Heat recovery certified by the Passivhaus Institut.

Good performance.



Heavy System Network TimberonLive

TimberOnLive

info@timberonlive.com

http://www.timberonlive.com

Product category : Opere strutturali / Sistema passivo

System of heavy wooden framework. Sealing line on the outside. Ventilated façade and roof finished in Siberian larch.

Good performance.

Costs

Construction and exploitation costs

Cost of studies : 3 000 € Total cost of the building : 184 117 €

Energy bill

Forecasted energy bill/year : 200,00 € Real energy cost/m2 : 1 Real energy cost/Dwelling : 200

Urban environment

The house is located on a plot of 1000.00 m2, in Muros de Nalon (Asturias), at an altitude of 127.00 m. and 1000 m. away from the Cantabrian Sea. The climate of the coastal area of Asturias is characterized as mild-tempered, with abundant rainfall throughout the year and mild temperatures in both winter and summer. The average winter temperature is 9 ° C-10 ° C and 18 ° C-19 ° C in summer .

Land plot area

Land plot area : 1 000,00 m²

Built-up area

Built-up area : 20,00 %

Green space

Green space : 800,00




Building Environmental Quality

- indoor air quality and health
- acoustics
- comfort (visual, olfactive, thermal)
- energy efficiency
- maintenance
- building process
- products and materials

Contest

Building candidate in the category



Premio de los usuarios



Date Export : 20230519024642